UNIVERSAL HOLDING ELECTROMAGNETS

Export Product-list
January 2018

TECNODINAMICA®

TECHNICAL CHARACTERISTICS FAIL-SAFE: unlock immediately upon removal of power. CRUSH SAFE: the "open-door" command operates (doesn't jam) even if crowds are crushing the door (in frontal striking configuration X).	**STRIKING CONFIGURATION** X = Front locking Z = Shear locking)	**HOLDING FORCE** 10 Newton = 0,98 kg kg/Nw	**UNIVERSAL OPERATING VOLTAGE** or P version, define 12 or 24V Vdc	**CURRENT DRAW** mA	**ELECTRONIC MONITORING**				**Ordering information** MODELS		**Q.ty** N°
					MAGNETIC BOND SENSOR to control holding force	**V** = Green led **R** = Red led	**BUILT-IN RELAY** 1 SPDT contact - 1A/30V in changeover	**W** = PG7 cable gland in tin **I** = Flush mounting **S** = Surface mounting			
SLIM-SENTRYLOCK for front mounting 	X	300/3000	12/24V	500/250	●	---	●	I	**002075B33I**	strike plate not included	
SLIM-SENTRYLOCK surface mounting 	X	300/3000	12/24V	500/250	●	●	●	S	**002075B33S**		
SLIM-SENTRYLOCK watertight 	X	300/3000	12/24V	500/250	●	---	●	W	**002075B33H**		
MEDISENTRYLOCK semplified	X X X	180/1800 150/1500 125/1250	12/24V 12/24V 12/24V	420/210 240/120 150/70	--- --- ---	--- --- ---	--- --- ---	S S S	**002083A39Y** **002083A37Y** (on request) **002083A30Y** (on request)		
MINISENTRYLOCK 	X	70/700	12/24V	340/165	---	---	---	S	**0020804A2UY**		
ACCESSORIES											
STRIKE PLATE		**MANDATORY - accessory to be coupled to:**					**STRIKING CONFIGURATION**				
SLIM-MONOFACE 	X1	SLIM-SENTRYLOCK For all models – recessed/surface-mount/waterproof					FRONTAL (SLIM-MONOFACE)		**0020750X1**		
MEDIFACE 	X1	MEDISENTRYLOCK					FRONTAL (MEDIFACE)		**0020800X1**		
MINIFACE 	X1	MINISENTRYLOCK					FRONTAL (MINIFACE))		**0020700X1**		
ANGULAR BRACKETS		**OPTIONAL - accessory to be coupled to:**					**STRIKING CONFIGURATION**				
LS 	L1	"L-shaped" anodised aluminium corner bracket for surface-mounted SLIM-SENTRYLOCK							**0020750L1**		
I 	L1	"L-shaped" anodised aluminium corner bracket for waterproof SLIM-SENTRYLOCK							**0020750I1**		
LZ2 	LZ2	"Z-shaped" anodised aluminium pair of corner brackets for surface-mount/water-proof SLIM-SENTRYLOCK							**0020750Z2**		
PZ 	P1 P2	a self-adhesive screw cover plate for "L-shaped" corner bracket (excluding bracket) Set of two self-adhesive screw cover plates for "Z-shaped" corner brackets (excluding brackets)							**0020750M1** **0020750M2**		
F 	F	Special bracket for surface-mounted SLIM-SENTRYLOCK fire doors							**0020750F1**		
G 	U1	"Star-shaped" anodised aluminium brackets for SLIM-SENTRYLOCK glass doors							**0020750G1**		
U	U1	"U-shaped" anodised aluminium bracket for SLIM-SENTRYLOCK sliding doors							**0020750S1**		
LM	L1	"L-shaped" anodised aluminium corner bracket for floor-mount (or other) MEDISENTRYLOCK							**0020800L1**		
Z	LZ2	Pair of "Z-shaped" angular brackets in anodised aluminium for MINISENTRYLOCK							**0020804Z2**		
G 	U1	"Star-shaped" brackets for doors in glass only in anodised aluminium for MINISENTRYLOCK							**0020804G1**		

Note: The published products of holding electromagnets do **not include** the accessories. Particularly do not forget to order the proper strike that is mandatory for the operation of any electromagnet.