

SLIM-DUALUX PROFESSIONAL STOP/GO DISPLAYS

Export Product-list
January 2018








TECNODIMENSIONE®

- With 2 screw-on terminal boxes for conventional wiring
- Green/red lights + buzzer + multifunctional push button with "dry" changeover contacts (no voltage).
- 1 self-adhesive cover in polycarbonate, 180 x 30 mm, R2,5, thickness 0.3 mm with international symbols, available in 7 colours.

Ordering information



Q.ty

Assembly type	Models for 12Vdc/70mA power supply	MODELS	N°
Assembly type 1 fully aligned concealed for recess-mounting without flange on the same plane of the door frame panel * 	SLIM-DUALUX stop and go display type 1 with fully aligned concealed for recess-mounting on the same plane of the door frame panel without flange. Ideal to achieve a "smooth" surface (without roughness) that is easy to clean. Supplied with diffuser screen and gap G for sections with a thickness of 1.6mm. Complete with self-adhesive cover designed to be applied after the final installation of the system. * In this case it is advisable to prepare the recess during the door frame machining.	034981CM2U	
	Same with diffuser screen and gap G for sections with a thickness of 3mm.	034981CM2U3	
	Models for 24Vdc/40mA power supply (on request)		
	SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply with diffuser screen with G gap for sections with a thickness of 1.6mm	034981CM4U	
	Same with diffuser screen and gap G for sections with a thickness of 3mm.	034981CM4U3	
Assembly type 2 fully aligned at milling for recess-mounting with front flange on the same plane of the panel surface ♦ 	Models for 12Vdc/70mA power supply SLIM-DUALUX stop and go display type 2 for aligned recessed flush fitting in bottom of panel using front flange (e.g. To mount on wall panel next to the door frame on the post where no chasing can be carried out). Supplied with front flange in anodized aluminium with "silver" finish - 250x50mm, thickness 2.5mm for recessmounting on the same plane of the panel surface for aligned recessed flush fitting in bottom of plane using front flange. Cover pre-assembled and fixed into the flange niche. ♦ In this case, it is advisable to prepare sunk milling during the panel machining phase.	034982CM2U	
	Models for 24Vdc/40mA power supply (on request)		
	SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply.	034982CM4U	
Assembly type 3 for conventional flush mounting with front flange overlapping door frame 	Models for 12Vdc/70mA power supply SLIM-DUALUX stop and go display type 3 for traditional recessed fitting using flange. Supplied with front flange in anodized aluminium with "silver" finish - 250x50mm, thickness 4mm for flush mounting. Cover pre-assembled and fixed into the flange niche. Mounting can be carried out "on site", directly onto the installed door frame.	034983CM2U	
	Models for 24Vdc/40mA power supply (on request)		
	SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply	034983CM4U	
Assembly type 4 for surface mounting with using housing 	Models for 12Vdc/70mA power supply SLIM-DUALUX stop and go display type 4 for mounting placed on surface using housing. With extra-strong protective housing, made in anodized silver finish aluminium (35x25x215mm). Self-adhesive cover in polycarbonate, provided separately and designed to be used as final cover to hide the 4 fixing screws of the housing on the door frame. Useful when you wish to avoid recess-mounting or cuts on the door frame.	034984CM2U	
	Models for 24Vdc/40mA power supply (on request)		
	SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply.	034984CM4U	
Assembly type 5 for recessed wall-mounting with flange and wall-mounting receptacle 	Models for 12Vdc/70mA power supply SLIM-DUALUX stop and go display type 5 for recessed assembly using flange and wall box. Supplied with front flange in anodized aluminium with "silver" finish - 250x50mm, thickness 4mm, to be fixed to the housing by placing on wall surface. Self-adhesive cover in polycarbonate pre-assembled and fixed into the flange niche. Also fitted with wall box with "wings" for rapid anchoring (65x30x230mm), in plastic taken from single block to be assembled "in a niche" in the wall to house the body of the stop and go display. Wall niche and cable channel to be prepared beforehand.	034985CM2U	
	Modelli per alimentazione 24Vdc/40mA (a richiesta)		
	SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply.	034985CM4U	

Special configurations available at extra charge: Cover with your logo and/or customized.

For sizes, measurements and details of chasing, application examples and connection diagrams, see page 15.

SLIM-DUALUX STOP & GO DISPLAYS - sizes, application examples and connection diagram

