






	<div>SLIM-DUALUX PROFESSIONAL STOP/GO DISPLAYS</div> <div><ul style="list-style-type: none">- With 2 "screw-type" terminal boards for conventional cables- Green/red light + buzzer + multifunctional push button with "dry" changeover contacts (no voltage).- 1 self-adhesive cover in polycarbonate, 180 x 30 mm, R2,5, thickness 0.3 mm with international symbols, available in 7 colours.</div>	<div>Export Product-list January 2018</div> <div> TECNODIMENSIONE®</div> <div><div>Ordering information </div><div></div><div>Q.ty</div></div>		
<div>Assembly type 1 fully aligned concealed for recess-mounting without flange on the same plane of the door frame panel ✱</div> <div></div>	<div>Models for 12Vdc/70mA power supply</div> <div>SLIM-DUALUX stop and go display type 1 with fully aligned concealed for recess-mounting on the same plane of the door frame panel without flange. Ideal to achieve a "smooth" surface (without roughness) that is easy to clean. Supplied with diffuser screen and gap G for sections with a thickness of 1.6 mm. Complete with self-adhesive cover designed to be applied after the final installation of the system. ✱ In this case it is advisable to prepare the recess during the door frame machining.</div> <div>Same with diffuser screen and gap G for sections with a thickness of 3 mm.</div> <div>Models for 24Vdc/40mA power supply (on request)</div> <div>SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply with diffuser screen with G gap for sections with a thickness of 1.6 mm</div> <div>Same with diffuser screen and gap G for sections with a thickness of 3 mm</div>	<div>MODELS</div> <div>034981CM2U</div> <div>034981CM2U3</div> <div>034981CM4U</div> <div>034981CM4U3</div>		<div>N°</div>
<div>Assembly type 2 fully aligned at milling for recess-mounting with front flange on the same plane of the panel surface ♦</div> <div></div>	<div>Models for 12Vdc/70mA power supply</div> <div>SLIM-DUALUX stop and go display type 2 for aligned recessed flush fitting in bottom of panel using front flange (e.g. To mount on wall panel next to the door frame on the post where no chasing can be carried out). Supplied with front flange in anodized aluminium with "silver" finish - 250 x 50 mm, thickness 2.5 mm for recess-mounting on the same plane of the panel surface for aligned recessed flush fitting in bottom of plane using front flange. Cover pre-assembled and fixed into the flange niche. ♦ In this case, it is advisable to prepare sunk milling during the panel machining phase.</div> <div>Models for 24Vdc/40mA power supply (on request)</div> <div>SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply</div>	<div>MODELS</div> <div>034982CM2U</div> <div>034982CM4U</div>		<div>N°</div>
<div>Assembly type 3 for conventional flush mounting with front flange overlapping door frame</div> <div></div>	<div>Models for 12Vdc/70mA power supply</div> <div>SLIM-DUALUX stop and go display type 3 for traditional recessed fitting using flange. Supplied with front flange in anodized aluminium with "silver" finish - 250 x 50mm, thickness 4 mm for flush mounting. Cover pre-assembled and fixed into the flange niche. Mounting can be carried out "on site", directly onto the installed door frame.</div> <div>Models for 24Vdc/40mA power supply (on request)</div> <div>SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply</div>	<div>MODELS</div> <div>034983CM2U</div> <div>034983CM4U</div>		<div>N°</div>
<div>Assembly type 4 for surface mounting with using housing</div> <div></div>	<div>Models for 12Vdc/70mA power supply</div> <div>SLIM-DUALUX stop and go display type 4 for mounting placed on surface using housing. With extra-strong protective housing, made in anodized silver finish aluminium (35 x 25 x 215 mm). Self-adhesive cover in polycarbonate, provided separately and designed to be used as final cover to hide the 4 fixing screws of the housing on the door frame. Useful when you wish to avoid recess-mounting or cuts on the door frame.</div> <div>Models for 24Vdc/40mA power supply (on request)</div> <div>SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply</div>	<div>MODELS</div> <div>034984CM2U</div> <div>034984CM4U</div>		<div>N°</div>
<div>Assembly type 5 for recessed wall-mounting with flange and wall-mounting receptacle</div> <div></div>	<div>Models for 12Vdc/70mA power supply</div> <div>SLIM-DUALUX stop and go display type 5 for recessed assembly using flange and wall box. Supplied with front flange in anodized aluminium with "silver" finish - 250 x 50 mm, thickness 4 mm, to be fixed to the housing by placing on wall surface. Self-adhesive cover in polycarbonate pre-assembled and fixed into the flange niche. Also fitted with wall box with "wings" for rapid anchoring (65 x 30 x 230 mm), in plastic taken from single block to be assembled "in a niche" in the wall to house the body of the stop and go display. Wall niche and cable channel to be prepared beforehand.</div> <div>Models for 24Vdc/40mA power supply (on request)</div> <div>SLIM-DUALUX stop and go display same but with 24 Vdc/40mA power supply</div>	<div>MODELS</div> <div>034985CM2U</div> <div>034985CM4U</div>		<div>N°</div>

Special configurations available at extra charge: Cover with your logo and/or customized.

For sizes, measurements and details of chasing, application examples and connection diagrams, see page 46.

Technical drawing of the SLIM-DUALUX Stop/Go display, showing front, side, and cross-section views with dimensions and labels.

Front View Dimensions:

- Overall height: 250 mm
- Overall width: 50 mm
- Flange width: 28 mm
- Top corner radius: R5
- Bottom corner radius: R4
- Bottom flange width: 4 mm

Side View Dimensions:

- Overall height: 230 mm
- Top flange width: 65 mm
- Bottom flange width: 36 mm
- Bottom flange thickness: 20 mm
- Max. depth: 10 mm

Cross-section View Dimensions:

- Overall height: 220 mm
- Diffuser screen height: 142 mm
- Push button height: 21 mm
- Max. depth: 21 mm

Labels and Components:

- Flange
- R5
- Screw-type terminal box for conventional applications
- Diffuser screen
- Buzzer
- 22
- 142
- Push button
- 21
- Max. depth
- Screw-type terminal box
- 4
- Cover
- SLIM-DUALUX Stop/Go display with flange inserted into the wall mounting receptacle
- Wall-mounting receptacle
- Flange flush with wall, fixed to wall-mounting receptacle
- Wall
- Raceway
- Clamping wings
- Cover fixed into the flange niche
- Use a 5 lead cable for conventional wiring

(overall dimensions in mm)

